

DEWALT®**POWER
SHIFT▶▶**

TACKLE PREPARATION APPLICATIONS ON DEMANDING CONCRETE JOBSITES

with the DEWALT POWERSHIFT™ Plate Compactor, delivering the high performance and productivity you expect in a 15 kN class plate compactor.

It operates with a powerful sealed brushless motor that requires no maintenance, and its handles have been ergonomically designed to help reduce vibration during long compaction cycles. These foldable handles feature highly intuitive controls including 2 speed settings which allow for precise compaction in various types of soil.

The DEWALT POWERSHIFT™ Plate Compactor also includes a 12 L gravity-fed water tank to help with dust suppression, and an integrated wheel kit makes transportation easy.

**NO PETROL.
NO CORDS.
NO JOB
TOO BIG.▶▶**



DEWALT POWERSHIFT™ PLATE COMPACTOR

GUARANTEED TOUGH.®**DCPS7154**

DEWALT POWERSHIFT™ PLATE COMPACTOR▶▶

**POWERED BY
DEWALT POWERSHIFT™
BATTERY**

**11 LITRE
WATER TANK**
Removable water tank and
gravity feed sprinkler included

**MAINTENANCE-FREE
BRUSHLESS MOTOR**

**MAINTENANCE-FREE ECCENTRIC
MASS**
Provides 100 Hz of
vibration & 15 kN of force.



*REQUIRES REGISTRATION WITHIN 30 DAYS OF PURCHASE. T&C'S APPLY.

**DEDICATED
LIFT POINT**
Integrated into roll
cage for lifting and
transporting plate
with machinery

**ERGONOMICALLY DESIGNED
FOLDING HANDLE**
Ergonomically designed handle for user
comfort. Folds for transport and can
be used in locked or unlocked position

**INTEGRATED
WHEEL KIT**
Wheel kit comes as
standard feature

**HANDLE MOUNTED
CONTROLS**
Allows user to activate
and deactivate without
releasing the handle

**DURABLE
400 MM STEEL
PLATE**
Features front and rear
curvatures for maximum
coverage



RELATED PRODUCTS



AF-O-VPF-0022D-012

**POWERSHIFT™
Rubber Mat**
(spare part, sold
separately)

DCBPS0554

**POWERSHIFT™
554 Wh Battery**



DCBPSC0550

**POWERSHIFT™
550 W Charger**

DCAFVPS

**POWERSHIFT™
XR FLEXVOLT®
Adaptor**



DCE6820N

**18V XR
Water Tank**

SPECIFICATIONS

MAX CENTRIFUGAL FORCE	High: 15 kN Low: 10 kN
MAX VIBRATION FREQUENCY	High: 6,000 VPM Low: 4,920 VPM
MAX FORWARD TRAVEL SPEED	High: 28 m/min Low: 22 m/min
MAX COVERAGE PER BATTERY CHARGE	244 m²
HAND ARM VIBRATION	1.5 m/s²
WORKING SURFACE	Full: 2200 m²/h Low: 1732 m²/h
SURFACE PRESSURE	Full: 15.5 PSI Low: 10.3 PSI
MACHINE L x W x H	70 x 40 x 67 cm
HANDLE HEIGHT x WIDTH	89 x 36 mm
BASE PLATE LENGTH x WIDTH	56 x 40 cm
GRADEABILITY	30%
MAX INCLINE	20°
SPEED SETTINGS	2
WEIGHT (TOOL ONLY)	94 kg



Copyright ©2025 DEWALT. The following are examples of trademarks for one or more DEWALT power tools and accessories: the yellow and black color scheme; the "D"-shaped air intake grille; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

ICDCPS7154SS

GUARANTEED TOUGH.®

www.DEWALT.com.au